SENATE BILL NO. 382–SENATORS PARKS AND KIHUEN (BY REQUEST)

MARCH 18, 2013

Referred to Committee on Education

SUMMARY—Revises provisions governing safety standards for school buses. (BDR 34-868)

FISCAL NOTE: Effect on Local Government: No. Effect on the State: No.

EXPLANATION - Matter in *bolded italics* is new; matter between brackets *fomitted material* is material to be omitted.

AN ACT relating to transportation of pupils; revising provisions relating to the flammability of certain materials and components used in new school buses; adopting standards for automatic systems of fire extinguishment for school buses that are so equipped; and providing other matters properly relating thereto.

Legislative Counsel's Digest:

Existing law provides that any new school bus purchased by a school district on 1 23456789 or after January 1, 2014, to transport pupils must meet certain standards relating to the flammability of occupant seating. (NRS 392.405) Section 2 of this bill changes the date for compliance with these standards to January 1, 2016. For any new school bus purchased on or after July 1, 2014, existing law also requires that plastic components in the engine compartment of the bus meet certain standards relating to flammability. (NRS 392.405) Section 2 likewise changes this date to July 1, 2016. Section 2 also provides for the use of alternative standards of flammability for certain plastic components which are directly exposed to heat and provides that, in 10 lieu of meeting standards of flammability, a new school bus purchased on or after 11 July 1, 2016, may be equipped with an automatic system of fire extinguishment that 12 13 meets certain requirements.

Existing law makes the fire safety standards described above applicable to any new school bus purchased by a private school to transport pupils. (NRS 394.190) Section 4 of this bill amends those provisions to correspond with those applicable to a school bus purchased by a school district.





THE PEOPLE OF THE STATE OF NEVADA, REPRESENTED IN SENATE AND ASSEMBLY, DO ENACT AS FOLLOWS:

Section 1. NRS 392.400 is hereby amended to read as follows:
 392.400 1. All vehicles used in the transportation of pupils
 must be:

(a) In good condition and state of repair.

5 (b) Well equipped, and must contain sufficient room and seats 6 so that the driver and each pupil being transported have a seat inside 7 the vehicle. Each pupil shall remain seated when the vehicle is in 8 motion.

9 (c) Inspected semiannually by the Department of Public Safety 10 to ensure that the vehicles are mechanically safe and meet the 11 minimum specifications established by the State Board. The 12 Department of Public Safety shall make written recommendations to 13 the superintendent of schools of the school district wherein any such 14 vehicle is operating for the correction of any defects discovered 15 thereby.

16 2. If the superintendent of schools fails or refuses to take 17 appropriate action to have the defects corrected within 10 days after 18 receiving notice of them from the Department of Public Safety, the 19 superintendent is guilty of a misdemeanor, and upon conviction 20 thereof may be removed from office.

3. Except as otherwise provided in subsection 4, all vehicles
used for transporting pupils must meet the specifications established
by regulation of the State Board.

4. Except as otherwise provided in [this] subsection [,] 5, any bus which is purchased and used by a school district to transport pupils to and from extracurricular activities is exempt from the specifications adopted by the State Board if the bus meets the federal safety standards for motor vehicles which were applicable at the time the bus was manufactured and delivered for introduction in interstate commerce. [On and after January 1, 2014, any]

5. *Any* new school bus which is purchased by a school district to transport pupils must meet the standards set forth in INRS 392.405.

34 5.]:

4

(a) Subsection 1 of NRS 392.405 if the school bus is purchased
 on or after January 1, 2016; and

37 (b) Subsection 2 or 3 of NRS 392.405 if the school bus is 38 purchased on or after July 1, 2016.

39 **6.** Any person violating any of the requirements of this section 40 is guilty of a misdemeanor.





1 **Sec. 2.** NRS 392.405 is hereby amended to read as follows:

2 392.405 1. On and after January 1, [2014,] 2016, with respect to any new school bus which is purchased by a school district to 3 transport pupils, the school bus must meet the following standards 4 5 in addition to being equipped as required by the regulations of the 6 State Board:

[1.] (a) Occupant seating within the school bus must be tested 7 8 in accordance with either:

(a) The ASTM International Standard ASTM E1537, 9 "Standard Test Method for Fire Testing of Upholstered Furniture"; 10 11 or

12 (b) (2) The School Bus Seat Upholstery Fire Block Test 13 established by the National School Transportation Specifications and Procedures adopted at the most recent National Congress on 14 15 School Transportation.

16 [2.] (b) For the purposes of subsection 1, paragraph (a) such 17 testing must be conducted on a complete seat assembly inside a test 18 room or school bus, and occupant seating shall be deemed to have 19 failed the ASTM E1537 test or Fire Block Test, as applicable, if:

(a) The seat assembly exhibits a weight loss of 3 pounds 20 21 or greater during the first 10 minutes of the test; or

22 (b) (2) The seat assembly exhibits a heat release rate of 80 23 kilowatts or greater.

24

13. Each 25 Except as otherwise provided in subsection 3, each plastic *2*. 26 component contained in the engine compartment of a new school bus which is purchased by a school district on and after July 1, 27 [2014,] 2016, to transport pupils must meet [a V-0 classification] 28 29 one of the following classifications when tested in accordance with the Underwriters Laboratories Inc. Standard 94, "the Standard for 30 31 Safety of Flammability of Plastic Materials for Parts in Devices and Appliances testing [...] ": 32

33

(a) A V-0 classification; or

(b) If the component is located within 100 millimeters directly 34 above an exhaust component that is not shielded, including, 35 without limitation, a catalytic converter, an exhaust gas 36 37 recirculation pipe that carries uncooled exhaust gas, an exhaust 38 *manifold or an exhaust pipe:*

39

(1) For molded parts, a V-0 classification; (2) For foams, an HF-1 classification; and

40 41

(3) For thin films, a VTM-0 classification.

42 3. In lieu of meeting the requirements set forth in subsection 2, a new school bus may be purchased by a school district on or 43 44 after July 1, 2016, to transport pupils if it meets the following 45 requirements:





1 (a) The school bus has an automatic system for fire 2 extinguishment in the engine compartment that includes a 3 mechanism for activation by the driver;

4 (b) Any nozzles for fire suppression are located, without 5 limitation, under the school bus, in the electrical panel or under 6 the dashboard, but are not located in the passenger compartment; 7 and

8 (c) The system for fire suppression includes a lamp or buzzer 9 to alert the driver when the system is activated.

10

Sec. 3. NRS 392.410 is hereby amended to read as follows:

11 392.410 1. Except as otherwise provided in this subsection, 12 every school bus operated for the transportation of pupils to or from 13 school must be equipped with:

(a) A system of flashing red lights of a type approved by the
State Board and installed at the expense of the school district or
operator. Except as otherwise provided in subsection 2, the driver
shall operate this signal:

18

(1) When the bus is stopped to unload pupils.

19 20

40

(2) When the bus is stopped to load pupils.(3) In times of emergency or accident when appropria

(3) In times of emergency or accident, when appropriate.

(b) A mechanical device, attached to the front of the bus which, 21 22 when extended, causes persons to walk around the device. The 23 device must be approved by the State Board and installed at the expense of the school district or operator. The driver shall operate 24 25 the device when the bus is stopped to load or unload pupils. The 26 installation of such a mechanical device is not required for a school 27 bus which is used solely to transport pupils with special needs who 28 are individually loaded and unloaded in a manner which does not 29 require them to walk in front of the bus. The provisions of this 30 paragraph do not prohibit a school district from upgrading or 31 replacing such a mechanical device with a more efficient and 32 effective device that is approved by the State Board.

A driver may stop to load and unload pupils in a designated
 area without operating the system of flashing red lights required by
 subsection 1 if the designated area:

36 (a) Has been designated by a school district and approved by the37 Department;

(b) Is of sufficient depth and length to provide space for the bus
to park at least 8 feet off the traveled portion of the roadway;

(c) Is not within an intersection of roadways;

41 (d) Contains ample space between the exit door of the bus and 42 the parking area to allow safe exit from the bus;

43 (e) Is located so as to allow the bus to reenter the traffic from its
 44 parked position without creating a traffic hazard; and





(f) Is located so as to allow pupils to enter and exit the bus 1 2 without crossing the roadway.

3. In addition to the equipment required by subsection 1 and 3 4 except as otherwise provided in subsection 4 of NRS 392.400, each 5 school bus must:

6 (a) Be equipped and identified as required by the regulations of 7 the State Board; and

8 (b) If the bus is a new bus purchased by a school district fon and 9 after January 1, 2014, to transport pupils, meet the standards set 10 forth in :

11 (1) Subsection 1 of NRS 392.405 H if the bus is purchased 12 on or after January 1, 2016; and

13 (2) Subsection 2 or 3 of NRS 392.405 if the bus is purchased on or after July 1, 2016. 14

15 The agents and employees of the Department of Motor 4. 16 Vehicles shall inspect school buses to determine whether the provisions of this section concerning equipment and identification 17 18 of the school buses have been complied with, and shall report any 19 violations discovered to the superintendent of schools of the school 20 district wherein the vehicles are operating.

21 5 If the superintendent of schools fails or refuses to take 22 appropriate action to correct any such violation within 10 days after 23 receiving notice of it from the Department of Motor Vehicles, the 24 superintendent is guilty of a misdemeanor, and upon conviction 25 must be removed from office.

Any person who violates any of the provisions of this 26 6. 27 section is guilty of a misdemeanor.

Sec. 4. NRS 394.190 is hereby amended to read as follows:

394.190 1. The provisions of NRS 392.400 and 392.410 29 30 relating to the condition, equipment and identification of vehicles 31 used for the transportation of pupils apply to private schools.

On and after January 1, [2014,] 2016, or July 1, 2016, as 32 2. 33 *applicable*, with respect to any new school bus purchased to transport pupils, the standards for school buses set forth in : 34 35

(a) Subsection 1 of NRS 392.405; and

(b) Subsection 2 or 3 of NRS 392.405,

37 → apply to private schools.

38 All such vehicles are subject to inspection at all times by 3. agents and employees of the Department of Motor Vehicles, who 39 40 shall report any violations discovered thereby to the executive head 41 of the private school.

4. If the executive head of the private school fails or refuses to 42 43 take appropriate action to correct any such violation within 10 days 44 after receiving the report from the Department of Motor Vehicles, 45 the executive head is guilty of a misdemeanor.



28

36





1



- 6 -